

## HOBRAFILT® - “NT” series depth filter sheets

### Characteristic

Hobrafilt® depth filter sheets are made of carefully selected and inspected materials, namely from various types of cellulose, high quality kieselguhr, perlites and specially treated resins. Filter sheet is in principle a three-dimensional depth filter that is characterized by the presence of adsorbents, compounds with a large internal surface.



### Application

Hobrafilt® filter sheets of the “NT” series were especially developed for economic use during filtration in the beverage, chemical and pharmaceutical industries. The sheet thickness and composition were designed to remove impurities during filtration from a typical production batch so that the sheets have the filtration capacity required for the given filtration. This practically eliminates the unused capacity of sheets and increases efficiency. In case of a high concentration of impurities, we recommend consulting the use of Hobrafilt® filter sheets of the “NT” series with our specialists.


### HOBRAFILT® - “NT” series depth filter sheets - overview:

Type of sheet	Nominal retention Micron	Flow rate l/m <sup>2</sup> /min. (at 100 kPa)	Thickness mm
ST 3 NT	0,2	32 - 48	2,9 - 3,1
ST 5 NT	0,3	55 - 85	2,9 - 3,1
ST 7 NT	0,4	100 - 140	2,9 - 3,1
S 10 NT	0,8	152 - 209	2,9 - 3,1
S 15 NT	2	220 - 270	2,9 - 3,1
S 20 NT	3	270 - 330	2,9 - 3,1
S 30 NT	4	330 - 385	2,9 - 3,1
S 40 NT	5	500 - 650	2,9 - 3,1
S 60 NT	6	860 - 1060	2,9 - 3,1
S 80 NT	8	1500 - 1850	2,9 - 3,1
S 100 NT	11	900 - 1300*	2,9 - 3,1
S 340 NT	25	1630 - 2100*	3,2 - 3,4
S 540 NT	<25	1915 - 3193**	3,8 - 4,2

\* at 30 kPa

\*\* at 20 kPa

Hobra – Školník s.r.o  
Smetanova ulice  
550 01 Broumov  
Czech Republic  
T: +420 491 580 111  
F: +420 491 580 140  
E: hobra@hobra.cz  
W: www.hobra.cz

Certifikace:  
ISO 9001   
ISO 14001

